


POLARIS



Descripción

Compact recessed downlight of only 30mm height with 20W, 25W and 30W power.

Body made of cast aluminum, with high dissipation performance that provides excellent heat dissipation.

IP20 degree of protection.

Opal diffuser with 120° opening and symmetrical light distribution, which provides homogeneous lighting over the entire surface.

Led chip SMD brand EPISTAR with Color Rendering Index 80 (CRI) that is supplied in color temperatures of 3000K, 4000K and 6000K.

LIFUD driver included with 0.95 power factor (PF).

Supply voltage 220-240V / 50-60Hz.

False ceiling mounting, adaptable to all types of modular and plaster ceilings.

Ceiling cut 205x205 mm.

Temperatures



Applications

Designed for general lighting applications in all kinds of common areas, offices and commercial use due to its efficient consumption.

Finishes

○ White

Version

*Optional dimmable DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC CASAMBI, BLUETOOTH AND ZIGBEE.

* Emergency Kit LHKIT2460



LIFUD® EPISTAR



CASAMBI



POLARIS 20

Reference	Consumption	Voltage	Temperature	Finish	Lumens		CRI	IP
ON-OFF								
LHDCP72030L	20W	AC220-240V	3000K	White	1800	120°	80	20
LHDCP72040L	20W	AC220-240V	4000K	White	1800	120°	80	20
LHDCP72060L	20W	AC220-240V	6000K	White	1800	120°	80	20



REGULACIONES

Reference	Consumption	Temperature	Reference	Consumption	Temperature
TRIAC					
LHDCP72030T	20W	3000K	LHDCP720300	20W	3000K
LHDCP72040T	20W	4000K	LHDCP720400	20W	4000K
LHDCP72060T	20W	6000K	LHDCP720600	20W	6000K
DALI					
LHDCP72030D	20W	3000K	LHDCP72030C	20W	3000K
LHDCP72040D	20W	4000K	LHDCP72040C	20W	4000K
LHDCP72060D	20W	6000K	LHDCP72060C	20W	6000K
BLUETOOTH					
LHDCP72030B	20W	3000K	LHDCP72030Z	20W	3000K
LHDCP72040B	20W	4000K	LHDCP72040Z	20W	4000K
LHDCP72060B	20W	6000K	LHDCP72060Z	20W	6000K
EMERGENCY					
LHDCP72030E	20W	3000K			
LHDCP72040E	20W	4000K			
LHDCP72060E	20W	6000K			

ACCESSORIES

LHMBGATZBBL	GATEWAY MULTICONTROLLER ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINARIES
LHMBGATZGET	GATEWAY MULTICONTROLLER ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINARIES.
LHMBPTRIACZG	PICKUP CONVERTER TRIAC - ZIGBEE 3.0 + PUSH MAX 150W.

Dimensions



Luminous Flux

