


POLARIS



Descripción

Compact recessed downlight of only 30mm height with 20W, 25W and 30W power.

Body made of cast aluminum, with high dissipation performance that provides excellent heat dissipation.

IP20 degree of protection.

Opal diffuser with 120° opening and symmetrical light distribution, which provides homogeneous lighting over the entire surface.

Led chip SMD brand EPISTAR with Color Rendering Index 80 (CRI) that is supplied in color temperatures of 3000K, 4000K and 6000K.

LIFUD driver included with 0.95 power factor (PF).

Supply voltage 220-240V / 50-60Hz.

False ceiling mounting, adaptable to all types of modular and plaster ceilings.

Ceiling cut 205x205 mm.

Temperatures



Applications

Designed for general lighting applications in all kinds of common areas, offices and commercial use due to its efficient consumption.

Finishes

○ White

Version

*Optional dimmable DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC CASAMBI, BLUETOOTH AND ZIGBEE.

* Emergency Kit LHKIT2460



LIFUD® EPISTAR



CASAMBI



POLARIS 30

Reference	Consumption	Voltage	Temperature	Finish	Lumens		CRI	IP
ON-OFF								
LHDCP73030L	30W	AC220-240V	3000K	White	2700	120°	80	20
LHDCP73040L	30W	AC220-240V	4000K	White	2700	120°	80	20
LHDCP73060L	30W	AC220-240V	6000K	White	2700	120°	80	20



REGULACIONES

Reference	Consumption	Temperature	Reference	Consumption	Temperature
TRIAC					
LHDCP73030T	30W	3000K	LHDCP730300	30W	3000K
LHDCP73040T	30W	4000K	LHDCP730400	30W	4000K
LHDCP73060T	30W	6000K	LHDCP730600	30W	6000K
DALI					
LHDCP73030D	30W	3000K	LHDCP73030C	30W	3000K
LHDCP73040D	30W	4000K	LHDCP73040C	30W	4000K
LHDCP73060D	30W	6000K	LHDCP73060C	30W	6000K
BLUETOOTH					
LHDCP73030B	30W	3000K	LHDCP73030Z	30W	3000K
LHDCP73040B	30W	4000K	LHDCP73040Z	30W	4000K
LHDCP73060B	30W	6000K	LHDCP73060Z	30W	6000K
EMERGENCY					
LHDCP73030E	30W	3000K			
LHDCP73040E	30W	4000K			
LHDCP73060E	30W	6000K			

ACCESSORIES

LHMBGATZBBL	GATEWAY MULTICONTROLLER ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINARIES
LHMBGATZGET	GATEWAY MULTICONTROLLER ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINARIES.
LHMBPTRIACZG	PICKUP CONVERTER TRIAC - ZIGBEE 3.0 + PUSH MAX 150W.

Dimensions



Luminous Flux

