

ZENIT II



Zenit II 7



Description

Recessed downlight with high visual comfort in 7W power, which makes it practical and versatile to illuminate spaces with important and demanding heights.

Body and ring made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 degree of protection. Reflector made of white finished aluminum and opal PMMA diffuser.

70° opening optics with low glare level and symmetrical light distribution, which provides homogeneous lighting over the entire surface.

Led chip SMD brand BRIDGELUX with Color Rendering Index 90 (CRI) that is supplied in color temperatures of 3000K, 4000K and 2700K (7w).

LIFUD driver included with 0.95 power factor (PF).

Supply voltage 220-240V / 50-60Hz.

False ceiling mounting, adaptable to all types of modular and plaster ceilings.

Ceiling cutout of Ø75 mm.

Temperatures



Applications

Designed for general lighting applications in all kinds of common areas, offices and commercial use due to its efficient consumption and visual comfort at great heights.

Finishes

○ White

* On demand it is supplied in any paint finish.

Version

* Optional dimmable DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC CASAMBI, BLUETOOTH AND ZIGBEE.

* Emergency Kit LHKIT2460



ZENIT II 7

Reference	Consumption	Voltage	Temperature	Finish	Lumens		CRI	IP
ON-OFF								
LHDT207BB27	7W	AC220-240V	2700K	White	570	70°	90	44
LHDT207BB30	7W	AC220-240V	3000K	White	570	70°	90	44
LHDT207BB40	7W	AC220-240V	4000K	White	570	70°	90	44
LHDT207NN27	7W	AC220-240V	2700K	Black	570	70°	90	44
LHDT207NN30	7W	AC220-240V	3000K	Black	570	70°	90	44
LHDT207NN40	7W	AC220-240V	4000K	Black	570	70°	90	44

REGULATIONS

Reference	Consumption	Temperature	Reference	Consumption	Temperature
-----------	-------------	-------------	-----------	-------------	-------------

TRIAC

LHDT207BB27T	7W	2700K
LHDT207BB30T	7W	3000K
LHDT207BB40T	7W	4000K
LHDT207NN27T	7W	2700K
LHDT207NN30T	7W	3000K
LHDT207NN40T	7W	4000K

DAU

LHDT207BB27D	7W	2700K
LHDT207BB30D	7W	3000K
LHDT207BB40D	7W	4000K
LHDT207NN27D	7W	2700K
LHDT207NN30D	7W	3000K
LHDT207NN40D	7W	4000K

EMERGENCY

LHDT207BB27E	7W	2700K
LHDT207BB30E	7W	3000K
LHDT207BB40E	7W	4000K
LHDT207NN27E	7W	2700K
LHDT207NN30E	7W	3000K
LHDT207NN40E	7W	4000K

0-10V

LHDT207BB270	7W	2700K
LHDT207BB300	7W	3000K
LHDT207BB400	7W	4000K
LHDT207NN270	7W	2700K
LHDT207NN300	7W	3000K
LHDT207NN400	7W	4000K

BLUETOOTH

LHDT207BA27B	7W	2700K
LHDT207BA30B	7W	3000K
LHDT207BA40B	7W	4000K
LHDT207NN27B	7W	2700K
LHDT207NN30B	7W	3000K
LHDT207NN40B	7W	4000K



ZIGBEE

LHDT207BB27Z	7W	2700K
LHDT207BB30Z	7W	3000K
LHDT207BB40Z	7W	4000K
LHDT207NN27Z	7W	2700K
LHDT207NN30Z	7W	3000K
LHDT207NN40Z	7W	4000K

ACCESSORIES

LHPTC181224	SIGNAL CONVERTER PICKUP TRIAC TO CASAMBI MAX. 150W
LHMBGATZBBL	GATEWAY MULTICONTROLLER ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINARIES
LHMBGATZGET	GATEWAY MULTICONTROLLER ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINARIES.
LHMBPTRIACZG	PICKUP CONVERTER TRIAC - ZIGBEE 3.0 + PUSH MAX 150W.

Dimensions



Luminous Flux

