



BALL

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHLBM155N27100	5W	DC48V	2700K	Black	330	360°	90	20
LHLBM155N27130	5W	DC48V	2700K	Black	360	360°	90	20
LHLBM155N27200	5W	DC48V	2700K	Black	390	360°	90	20
LHLBM155N30100	5W	DC48V	3000K	Black	330	360°	90	20
LHLBM155B30100	5W	DC48V	3000K	White	330	360°	90	20
LHLBM155N30130	5W	DC48V	3000K	Black	360	360°	90	20
LHLBM155B30130	5W	DC48V	3000K	White	360	360°	90	20
LHLBM155N30200	5W	DC48V	3000K	Black	390	360°	90	20
LHLBM155B30200	5W	DC48V	3000K	White	390	360°	90	20
DALI								
LHLBM155N27100D	5W	DC48V	2700K	Black	330	360°	90	20
LHLBM155N27130D	5W	DC48V	2700K	Black	360	360°	90	20
LHLBM155N27200D	5W	DC48V	2700K	Black	390	360°	90	20
LHLBM155N30100D	5W	DC48V	3000K	Black	330	360°	90	20
LHLBM155N30130D	5W	DC48V	3000K	Black	360	360°	90	20
LHLBM155N30200D	5W	DC48V	3000K	Black	390	360°	90	20
BLUETOOTH - CCT								
LHLBM155NTN10TB	5W	DC48V	2700K ~ 6000K	Black	330	360°	90	20
LHLBM155BTN10TB	5W	DC48V	2700K ~ 6000K	White	330	360°	90	20
LHLBM155NTN13TB	5W	DC48V	2700K ~ 6000K	Black	360	360°	90	20
LHLBM155BTN13TB	5W	DC48V	2700K ~ 6000K	White	360	360°	90	20
LHLBM155NTN20TB	5W	DC48V	2700K ~ 6000K	Black	390	360°	90	20
LHLBM155BTN20TB	5W	DC48V	2700K ~ 6000K	White	390	360°	90	20

*Luminaire compatible with TRACKS MAGNET XS DC48V SURFACE.

*Optional chip COB CRI92 in 2200K - 3500K - 4000K - 5000K - 6000K



Dimensions



Ø130 mm