



BALL SUSPENDED

Reference	Consumption	Voltage	Temperature	Color	Lumens	Α	CRI	IP
ON-OFF								
LHLBMS155N27100	5W	DC48V	2700K	Black	330	360°	90	20
LHLBMS155N27130	5W	DC48V	2700K	Black	360	360°	90	20
LHLBMS155N27200	5W	DC48V	2700K	Black	390	360°	90	20
LHLBMS155N30100	5W	DC48V	3000K	Black	330	360°	90	20
LHLBMS155B30100	5W	DC48V	3000K	White	330	360°	90	20
LHLBMS155N30130	5W	DC48V	3000K	Black	360	360°	90	20
LHLBMS155B30130	5W	DC48V	3000K	White	360	360°	90	20
LHLBMS155N30200	5W	DC48V	3000K	Black	390	360°	90	20
LHLBMS155B30200	5W	DC48V	3000K	White	390	360°	90	20
DALI								
LHLBMS155N27100D	5W	DC48V	2700K	Black	330	360°	90	20
LHLBMS155N27130D	5W	DC48V	2700K	Black	360	360°	90	20
LHLBMS155N27200D	5W	DC48V	2700K	Black	390	360°	90	20
LHLBMS155N30100D	5W	DC48V	3000K	Black	330	360°	90	20
LHLBMS155N30130D	5W	DC48V	3000K	Black	360	360°	90	20
LHLBMS155N30200D	5W	DC48V	3000K	Black	390	360°	90	20
BLUETOOTH - CCT								
LHLBMS155NTN10TB	5W	DC48V	2700K ~ 6000K	Black	330	360°	90	20
LHLBMS155BTN10TB	5W	DC48V	2700K ~ 6000K	White	330	360°	90	20
LHLBMS155NTN13TB	5W	DC48V	2700K ~ 6000K	Black	360	360°	90	20
LHLBMS155BTN13TB	5W	DC48V	2700K ~ 6000K	White	360	360°	90	20
LHLBMS155NTN20TB	5W	DC48V	2700K ~ 6000K	Black	390	360°	90	20
LHLBMS155BTN20TB	5W	DC48V	2700K ~ 6000K	White	390	360°	90	20

*Luminaire compatible with TRACKS MAGNET XS DC48V SURFACE.
*Optional chip COB CRI92 in 2200K - 2700K - 3500K - 4000K - 5000K - 6000K



Dimensions



Ø100 mm