



TUBE FLEXIBLE

Reference	Consumption	Voltage	Temperature	Lumens	△	CRI	IP
ON-OFF							
LHARM15101027	10W	DC48V	2700K	600	36°	90	20
LHARM15252527	25W	DC48V	2700K	1500	36°	90	20
LHARM15405027	40W	DC48V	2700K	2400	36°	90	20
LHARM15101030	10W	DC48V	3000K	600	36°	90	20
LHARM15252530	25W	DC48V	3000K	1500	36°	90	20
LHARM15405030	40W	DC48V	3000K	2400	36°	90	20
DALI							
LHARM15101027D	10W	DC48V	2700K	600	36°	90	20
LHARM15252527D	25W	DC48V	2700K	1500	36°	90	20
LHARM15405027D	40W	DC48V	2700K	2400	36°	90	20
LHARM15101030D	10W	DC48V	3000K	600	36°	90	20
LHARM15252530D	25W	DC48V	3000K	1500	36°	90	20
LHARM15405030D	40W	DC48V	3000K	2400	36°	90	20
BLUETOOTH - CCT							
LHARM151010TNB	10W	DC48V	2700K ~ 6000K	600	36°	90	20
LHARM152525TNB	25W	DC48V	2700K ~ 6000K	1500	36°	90	20
LHARM154050TNB	40W	DC48V	2700K ~ 6000K	2400	36°	90	20

ACCESSORIES

LHARM15SPN Suspension 2 meters black

*Luminaire compatible with TRACKS MAGNET XS DC48V SURFACE.

*Cuttings are made per meter

Dimensions

