

HOOK



Description

Surface downlight with high visual comfort in 20W power.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Color

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK 20

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS2020BA30	20W	AC220-240V	3000K	White	2150	70°	90	44
LHDS2020BA40	20W	AC220-240V	4000K	White	2150	70°	90	44
LHDS2020NA30	20W	AC220-240V	3000K	Black	2150	70°	90	44
LHDS2020NA40	20W	AC220-240V	4000K	Black	2150	70°	90	44

REGULATIONS

Reference	Consumption	Temperature
-----------	-------------	-------------

TRIAC

LHDS2020BA30T	20W	3000K
LHDS2020BA40T	20W	4000K
LHDS2020NA30T	20W	3000K
LHDS2020NA40T	20W	4000K

DALI

LHDS2020BA30D	20W	3000K
LHDS2020BA40D	20W	4000K
LHDS2020NA30D	20W	3000K
LHDS2020NA40D	20W	4000K

CASAMBI

LHDS2020BA30C	20W	3000K
LHDS2020BA40C	20W	4000K
LHDS2020NA30C	20W	3000K
LHDS2020NA40C	20W	4000K

EMERGENCY

LHDS2020BA30E	20W	3000K
LHDS2020BA40E	20W	4000K
LHDS2020BA30E	20W	3000K
LHDS2020BA40E	20W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES TRIAC
LHMBPTRIAC2G	CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Reference	Consumption	Temperature
-----------	-------------	-------------

O-10V

LHDS2020BA300	20W	3000K
LHDS2020BA400	20W	4000K
LHDS2020NA300	20W	3000K
LHDS2020NA400	20W	4000K


BLUETOOTH

LHDS2020BA30B	20W	3000K
LHDS2020BA40B	20W	4000K
LHDS2020NA30B	20W	3000K
LHDS2020NA40B	20W	4000K

ZIGBEE

LHDS2020BA30Z	20W	3000K
LHDS2020BA40Z	20W	4000K
LHDS2020NA30Z	20W	3000K
LHDS2020NA40Z	20W	4000K

Dimensions



Luminous Flow

