

HOOK



Description

Surface downlight with high visual comfort in 20W, 25W, 30W, 40W and 50W power.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Color

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK 25

Reference	Consumption	Voltage	Temperature	Color	Lumens	Δ	CRI	IP
ON-OFF								
LHDS2025BA30	25W	AC220-240V	3000K	White	2500	70°	90	44
LHDS2025BA40	25W	AC220-240V	4000K	White	2500	70°	90	44
LHDS2025NA30	25W	AC220-240V	3000K	Black	2500	70°	90	44
LHDS2025NA40	25W	AC220-240V	4000K	Black	2500	70°	90	44

REGULATIONS

Reference	Consumption	Temperature
-----------	-------------	-------------

TRIAC

LHDS2025BA30T	25W	3000K
LHDS2025BA40T	25W	4000K
LHDS2025BA30T	25W	3000K
LHDS2025BA40T	25W	4000K

DALI

LHDS2025BA30D	25W	3000K
LHDS2025BA40D	25W	4000K
LHDS2025NA30D	25W	3000K
LHDS2025NA40D	25W	4000K

CASAMBI

LHDS2025BA30C	25W	3000K
LHDS2025BA40C	25W	4000K
LHDS2025NA30C	25W	3000K
LHDS2025NA40C	25W	4000K

EMERGENCY

LHDS2025BA30E	25W	3000K
LHDS2025BA40E	25W	4000K
LHDS2025NA30E	25W	3000K
LHDS2025NA40E	25W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES TRIAC
LHMBPTTRACZG	CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Reference	Consumption	Temperature
-----------	-------------	-------------

0-10V

LHDS2025BA300	25W	3000K
LHDS2025BA400	25W	4000K
LHDS2025BA300	25W	3000K
LHDS2025BA400	25W	4000K


BLUETOOTH

LHDS2025BA30B	25W	3000K
LHDS2025BA40B	25W	4000K
LHDS2025NA30B	25W	3000K
LHDS2025NA40B	25W	4000K

ZIGBEE

LHDS2025BA30Z	25W	3000K
LHDS2025BA40Z	25W	4000K
LHDS2025NA30Z	25W	3000K
LHDS2025NA40Z	25W	4000K

Dimensions



Luminous Flow

