

HOOK



Description

Surface downlight with high visual comfort in 30W power.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Color

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK 30

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS2030BA30	30W	AC220-240V	3000K	White	2980	70°	90	44
LHDS2030BA40	30W	AC220-240V	4000K	White	2980	70°	90	44
LHDS2030NA30	30W	AC220-240V	3000K	Black	2980	70°	90	44
LHDS2030NA40	30W	AC220-240V	4000K	Black	2980	70°	90	44

REGULATIONS

Reference	Consumption	Temperature
TRIAC		
LHDS2030BA30T	30W	3000K
LHDS2030BA40T	30W	4000K
LHDS2030NA30T	30W	3000K
LHDS2030NA40T	30W	4000K

DALI

LHDS2030BA30D	30W	3000K
LHDS2030BA40D	30W	4000K
LHDS2030NA30D	30W	3000K
LHDS2030NA40D	30W	4000K

CASAMBI

LHDS2030BA30C	30W	3000K
LHDS2030BA40C	30W	4000K
LHDS2030NA30C	30W	3000K
LHDS2030NA40C	30W	4000K

EMERGENCY

LHDS2030BA30E	30W	3000K
LHDS2030BA40E	30W	4000K
LHDS2030BA30E	30W	3000K
LHDS2030BA40E	30W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTTRACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Reference	Consumption	Temperature
0-10V		
LHDS2030BA300	30W	3000K
LHDS2030BA400	30W	4000K
LHDS2030NA300	30W	3000K
LHDS2030NA400	30W	4000K

BLUETOOTH

LHDS2030BA30B	30W	3000K
LHDS2030BA40B	30W	4000K
LHDS2030NA30B	30W	3000K
LHDS2030NA40B	30W	4000K

ZIGBEE

LHDS2030BA30Z	30W	3000K
LHDS2030BA40Z	30W	4000K
LHDS2030NA30Z	30W	3000K
LHDS2030NA40Z	30W	4000K

Dimensions



Luminous Flow

