

HOOK



Description

Surface downlight with high visual comfort in 40W power.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Color

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK 40

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS2040BA30	40W	AC220-240V	3000K	White	3800	70°	90	44
LHDS2040BA40	40W	AC220-240V	4000K	White	3800	70°	90	44
LHDS2040NA30	40W	AC220-240V	3000K	Black	3800	70°	90	44
LHDS2040NA40	40W	AC220-240V	4000K	Black	3800	70°	90	44

REGULATIONS

Reference	Consumption	Temperature
TRIAC		
LHDS2040BA30T	40W	3000K
LHDS2040BA40T	40W	4000K
LHDS2040NA30T	40W	3000K
LHDS2040NA40T	40W	4000K

DAU

LHDS2040BA30D	40W	3000K
LHDS2040BA40D	40W	4000K
LHDS2040NA30D	40W	3000K
LHDS2040NA40D	40W	4000K

CASAMBI

LHDS2040BA30C	40W	3000K
LHDS2040BA40C	40W	4000K
LHDS2040BA30C	40W	3000K
LHDS2040BA40C	40W	4000K

EMERGENCY

LHDS2040BA30E	40W	3000K
LHDS2040BA40E	40W	4000K
LHDS2040BA30E	40W	3000K
LHDS2040BA40E	40W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTTRIACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Reference	Consumption	Temperature
O-10V		
LHDS2040BA300	40W	3000K
LHDS2040BA400	40W	4000K
LHDS2040NA300	40W	3000K
LHDS2040NA400	40W	4000K


BLUETOOTH

LHDS2040BA30B	40W	3000K
LHDS2040BA40B	40W	4000K
LHDS2040BA30B	40W	3000K
LHDS2040BA40B	40W	4000K

ZIGBEE

LHDS2040BA30Z	40W	3000K
LHDS2040BA40Z	40W	4000K
LHDS2040BA30Z	40W	3000K
LHDS2040BA40Z	40W	4000K

Dimensions



Luminous Flow

