

HOOK II



Description

Surface downlight with high visual comfort in 20W power.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Colors

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK II 20

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS2020BB30	20W	AC220-240V	3000K	White	2150	70°	90	44
LHDS2020BB40	20W	AC220-240V	4000K	White	2150	70°	90	44
LHDS2020NN30	20W	AC220-240V	3000K	Black	2150	70°	90	44
LHDS2020NN40	20W	AC220-240V	4000K	Black	2150	70°	90	44

REGULATIONS

Reference	Consumption	Temperature
TRIAC		
LHDS2020BB30T	20W	3000K
LHDS2020BB40T	20W	4000K
LHDS2020NN30T	20W	3000K
LHDS2020NN40T	20W	4000K

DALI

LHDS2020BB30D	20W	3000K
LHDS2020BB40D	20W	4000K
LHDS2020BB30D	20W	3000K
LHDS2020BB40D	20W	4000K

CASAMBI

LHDS2020BB30C	20W	3000K
LHDS2020BB40C	20W	4000K
LHDS2020NN30C	20W	3000K
LHDS2020NN40C	20W	4000K

EMERGENCY

LHDS2020BB30E	20W	3000K
LHDS2020BB40E	20W	4000K
LHDS2020BB30E	20W	3000K
LHDS2020BB40E	20W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTRIACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Reference	Consumption	Temperature
0-10V		
LHDS2020BB300	20W	3000K
LHDS2020BB400	20W	4000K
LHDS2020NN300	20W	3000K
LHDS2020NN400	20W	4000K


BLUETOOTH

LHDS2020BB30B	20W	3000K
LHDS2020BB40B	20W	4000K
LHDS2020BB30B	20W	3000K
LHDS2020BB40B	20W	4000K

ZIGBEE

LHDS2020BB30Z	20W	3000K
LHDS2020BB40Z	20W	4000K
LHDS2020NN30Z	20W	3000K
LHDS2020NN40Z	20W	4000K

Dimensions



Luminous Flow

