

HOOK II



Description

Surface downlight with high visual comfort in 25W power.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Colors

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK II 25

Reference	Consumption	Voltage	Temperature	Color	Lumens	Δ	CRI	IP
ON-OFF								
LHDS2025BB30	25W	AC220-240V	3000K	White	2500	70°	90	44
LHDS2025BB40	25W	AC220-240V	4000K	White	2500	70°	90	44
LHDS2025NN30	25W	AC220-240V	3000K	Black	2500	70°	90	44
LHDS2025NN40	25W	AC220-240V	4000K	Black	2500	70°	90	44

REGULATIONS


Reference	Consumption	Temperature
TRIAC		
LHDS2025BB30T	25W	3000K
LHDS2025BB40T	25W	4000K
LHDS2025NN30T	25W	3000K
LHDS2025NN40T	25W	4000K
DALI		
LHDS2025BB30D	25W	3000K
LHDS2025BB40D	25W	4000K
LHDS2025NN30D	25W	3000K
LHDS2025NN40D	25W	4000K
CASAMBI		
LHDS2025BB30C	25W	3000K
LHDS2025BB40C	25W	4000K
LHDS2025NN30C	25W	3000K
LHDS2025NN40C	25W	4000K
EMERGENCY		
LHDS2025BB30E	25W	3000K
LHDS2025BB40E	25W	4000K
LHDS2025NN30E	25W	3000K
LHDS2025NN40E	25W	4000K

Reference	Consumption	Temperature
0-10V		
LHDS2025BB300	25W	3000K
LHDS2025BB400	25W	4000K
LHDS2025NN300	25W	3000K
LHDS2025NN400	25W	4000K
BLUETOOTH		
LHDS2025BB30B	25W	3000K
LHDS2025BB40B	25W	4000K
LHDS2025NN30B	25W	3000K
LHDS2025NN40B	25W	4000K
ZIGBEE		
LHDS2025BB30Z	25W	3000K
LHDS2025BB40Z	25W	4000K
LHDS2025NN30Z	25W	3000K
LHDS2025NN40Z	25W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTRIACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Dimensions



Luminous Flow

