

HOOK II



Description

Surface downlight with high visual comfort in 30W power.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Colors

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK II 30

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS2030BB30	30W	AC220-240V	3000K	White	2980	70°	90	44
LHDS2030BB40	30W	AC220-240V	4000K	White	2980	70°	90	44
LHDS2030NN30	30W	AC220-240V	3000K	Black	2980	70°	90	44
LHDS2030NN40	30W	AC220-240V	4000K	Black	2980	70°	90	44

REGULATIONS


Reference	Consumption	Temperature
TRIAC		
LHDS2030BB30T	30W	3000K
LHDS2030BB40T	30W	4000K
LHDS2030NN30T	30W	3000K
LHDS2030NN40T	30W	4000K
DALI		
LHDS2030BB30D	30W	3000K
LHDS2030BB40D	30W	4000K
LHDS2030NN30D	30W	3000K
LHDS2030NN40D	30W	4000K
CASAMBI		
LHDS2030BB30C	30W	3000K
LHDS2030BB40C	30W	4000K
LHDS2030NN30C	30W	3000K
LHDS2030NN40C	30W	4000K
EMERGENCY		
LHDS2030BB30E	30W	3000K
LHDS2030BB40E	30W	4000K
LHDS2030NN30E	30W	3000K
LHDS2030NN40E	30W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTTRIACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Reference	Consumption	Temperature
0-10V		
LHDS2030BB300	30W	3000K
LHDS2030BB400	30W	4000K
LHDS2030NN300	30W	3000K
LHDS2030NN400	30W	4000K
BLUETOOTH		
LHDS2030BB30B	30W	3000K
LHDS2030BB40B	30W	4000K
LHDS2030NN30B	30W	3000K
LHDS2030NN40B	30W	4000K
ZIGBEE		
LHDS2030BB30Z	30W	3000K
LHDS2030BB40Z	30W	4000K
LHDS2030NN30Z	30W	3000K
LHDS2030NN40Z	30W	4000K

Dimensions



Luminous Flow

