

HOOK II



Description

Surface downlight with high visual comfort in 40W.

Body made of stove-enameled sheet metal with heatsink and luminaire structure made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP44 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

70° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Colors

○ White

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK II 40

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS2040BB30	40W	AC220-240V	3000K	White	3800	70°	90	44
LHDS2040BB40	40W	AC220-240V	4000K	White	3800	70°	90	44
LHDS2040NN30	40W	AC220-240V	3000K	Black	3800	70°	90	44
LHDS2040NN40	40W	AC220-240V	4000K	Black	3800	70°	90	44

REGULATIONS

Reference	Consumption	Temperature
TRIAC		
LHDS2040BB30T	40W	3000K
LHDS2040BB40T	40W	4000K
LHDS2040NN30T	40W	3000K
LHDS2040NN40T	40W	4000K

DALI

LHDS2040BB30D	40W	3000K
LHDS2040BB40D	40W	4000K
LHDS2040NN30D	40W	3000K
LHDS2040NN40D	40W	4000K

CASAMBI

LHDS2040BB30C	40W	3000K
LHDS2040BB40C	40W	4000K
LHDS2040NN30C	40W	3000K
LHDS2040NN40C	40W	4000K

EMERGENCY

LHDS2040BB30E	40W	3000K
LHDS2040BB40E	40W	4000K
LHDS2040NN30E	40W	3000K
LHDS2040NN40E	40W	4000K

ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128
LHMBGATZGET	LUMINAIRES GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128
LHMBPTTRIACZG	LUMINAIRES TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Reference	Consumption	Temperature
O-10V		
LHDS2040BB300	40W	3000K
LHDS2040BB400	40W	4000K
LHDS2040NN300	40W	3000K
LHDS2040NN400	40W	4000K


BLUETOOTH

LHDS2040BB30B	40W	3000K
LHDS2040BB40B	40W	4000K
LHDS2040NN30B	40W	3000K
LHDS2040NN40B	40W	4000K

ZIGBEE

LHDS2040BB30Z	40W	3000K
LHDS2040BB40Z	40W	4000K
LHDS2040NN30Z	40W	3000K
LHDS2040NN40Z	40W	4000K

Dimensions



Luminous Flow

