

HOOK XS



Description

Surface downlight with high visual comfort and 12W power.

Body made of stove-enamelled sheet metal with heatsink and the luminaire structure is made of cast aluminum with high dissipation performance that provides excellent heat dissipation.

IP54 protection grade.

Reflector manufactured in bright anodized aluminum and opal PMMA diffuser.

36° aperture optics with low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

BRIDGELUX brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K and 4000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 220-240V / 50-60Hz.

Surface mounting.

Temperature



Usage

Designed for general lighting applications for both domestic and commercial use due to its efficient consumption and visual comfort at great heights.

Colors

○ White ● Black

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.

*Emergency Kit LHKIT2460 see information page 415.



HOOK XS

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS1512N22	12W	AC220-240V	2200K	Black	1075	36°	95	54
LHDS1512N27	12W	AC220-240V	2700K	Black	1075	36°	95	54
LHDS1512N30	12W	AC220-240V	3000K	Black	1075	36°	95	54
LHDS1512N32	12W	AC220-240V	3200K	Black	1075	36°	95	54
LHDS1512N35	12W	AC220-240V	3500K	Black	1075	36°	95	54
LHDS1512N40	12W	AC220-240V	4000K	Black	1075	36°	95	54
LHDS1512N50	12W	AC220-240V	5000K	Black	1075	36°	95	54
LHDS1512N60	12W	AC220-240V	6000K	Black	1075	36°	95	54
LHDS1512B22	12W	AC220-240V	2200K	White	1075	36°	95	54
LHDS1512B27	12W	AC220-240V	2700K	White	1075	36°	95	54
LHDS1512B30	12W	AC220-240V	3000K	White	1075	36°	95	54
LHDS1512B32	12W	AC220-240V	3200K	White	1075	36°	95	54
LHDS1512B35	12W	AC220-240V	3500K	White	1075	36°	95	54
LHDS1512B40	12W	AC220-240V	4000K	White	1075	36°	95	54
LHDS1512B50	12W	AC220-240V	5000K	White	1075	36°	95	54
LHDS1512B60	12W	AC220-240V	6000K	White	1075	36°	95	54

REGULATIONS


TRIAC

LHDS1512N22T	12W	AC220-240V	2200K	Black	1075	36°	95	54
LHDS1512N27T	12W	AC220-240V	2700K	Black	1075	36°	95	54
LHDS1512N30T	12W	AC220-240V	3000K	Black	1075	36°	95	54
LHDS1512N32T	12W	AC220-240V	3200K	Black	1075	36°	95	54
LHDS1512N35T	12W	AC220-240V	3500K	Black	1075	36°	95	54
LHDS1512N40T	12W	AC220-240V	4000K	Black	1075	36°	95	54
LHDS1512N50T	12W	AC220-240V	5000K	Black	1075	36°	95	54
LHDS1512N60T	12W	AC220-240V	6000K	Black	1075	36°	95	54
LHDS1512B22T	12W	AC220-240V	2200K	White	1075	36°	95	54
LHDS1512B27T	12W	AC220-240V	2700K	White	1075	36°	95	54
LHDS1512B30T	12W	AC220-240V	3000K	White	1075	36°	95	54
LHDS1512B32T	12W	AC220-240V	3200K	White	1075	36°	95	54
LHDS1512B35T	12W	AC220-240V	3500K	White	1075	36°	95	54
LHDS1512B40T	12W	AC220-240V	4000K	White	1075	36°	95	54
LHDS1512B50T	12W	AC220-240V	5000K	White	1075	36°	95	54
LHDS1512B60T	12W	AC220-240V	6000K	White	1075	36°	95	54

ACCESSORIES

LHDS1512R15	15 DEGREE OPTICS
LHDS1512R24	24 DEGREE OPTICS
LHDS1512R50	50 DEGREE OPTICS
LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTTRIACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Dimensions



Luminous Flow

