

ONYX LINEAL



Description

Recessed, linear downlight with a high level of visual comfort formed by individual 6w, optical modules with a super-small longitudinal design.

Body made of die-cast aluminum with high dissipation performance that provides excellent heat evacuation.

IP20 protection grade

Reflector made of polycarbonate and different decorative finishes guaranteeing minimum glare.

38° aperture lens with UGR<12 low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperatures of 2700K, 3200K and 4000K.

Driver included with power factor 0.90(PF).

Voltage supply 220-240V / 50-60Hz.

Mounting in false ceilings adaptable to all types of modular and plaster ceilings.

Temperature



Usage

Designed for general and accent lighting applications that integrates into all types of modern, domestic, hotel, commercial, restaurant, office and residential spaces.

Colors

● Black - White

● White - Black

○ White - White

○ Transparente

● Black - Black

● White - Gold

● Black - Gold

Versions

* Optional adjustment, Dali, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.



ONYX 6 LINEAL

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHOL16BCCT	6W	AC220-240V	2700K ~3200K~ 4000K	White	375	38°	90	20
LHOL16NCCT	6W	AC220-240V	2700K ~3200K~ 4000K	Black	375	38°	90	20

REGULATIONS

TRIAC

Reference	Temperature	Color
LHOL16BCCTT	2700K ~3200K~ 4000K	White
LHOL16NCCTT	2700K ~3200K~ 4000K	Black

DALI

Reference	Temperature	Color
LHOL16BCCTD	2700K ~3200K~ 4000K	White
LHOL16NCCTD	2700K ~3200K~ 4000K	Black

BLUETOOTH

Reference	Temperature	Color
LHOL16BCCTB	2700K ~3200K~ 4000K	White
LHOL16NCCTB	2700K ~3200K~ 4000K	Black

ZIGBEE

Reference	Temperature	Color
LHOL16BCCTZ	2700K ~3200K~ 4000K	White
LHOL16NCCTZ	2700K ~3200K~ 4000K	Black

CASAMBI

Reference	Temperature	Color
LHOL16BCCTC	2700K ~3200K~ 4000K	White
LHOL16NCCTC	2700K ~3200K~ 4000K	Black

0-10V

Reference	Temperature	Color
LHOL16BCCT0	2700K ~3200K~ 4000K	White
LHOL16NCCT0	2700K ~3200K~ 4000K	Black

DALI + CCT

Reference	Temperature	Color
LHOL16BCCTND	2700K ~3200K~ 4000K	White
LHOL16NCCTND	2700K ~3200K~ 4000K	Black

BLUETOOTH + CCT

Reference	Temperature	Color
LHOL16BCCTNB	2700K ~3200K~ 4000K	White
LHOL16NCCTNB	2700K ~3200K~ 4000K	Black

ZIGBEE + CCT

Reference	Temperature	Color
LHOL16BCCTNZ	2700K ~3200K~ 4000K	White
LHOL16NCCTNZ	2700K ~3200K~ 4000K	Black


CASAMBI + CCT

Reference	Temperature	Color
LHOL16BCCTTNC	2700K ~3200K~ 4000K	White
LHOL16NCCTTNC	2700K ~3200K~ 4000K	Black

ACCESSORIES

LHROLR16BB Reflector round onyx linear 3 points	White - White
LHROLR16BN Reflector round onyx linear 3 points	White - Black
LHROLR16BO Reflector round onyx linear 3 points	White - Gold
LHROLR16NN Reflector round onyx linear 3 points	Black - Black
LHROLR16NO Reflector round onyx linear 3 points	Black - Gold
LHROLC16B Reflector square onyx linear 3 points	White
LHROLC16N Reflector square onyx linear 3 points	Black
LHROLC16T Reflector square onyx linear 3 points	Transparent

Dimensions



Luminous Flow

