



MATRIX LINEAR

Reference	Consumption	Voltage	Temperature	Color	Lumens	Δ	CRI	IP
ON-OFF								
LHLMM156N27	6W	DC48V	2700K	Black	460	36°	90	20
LHLMM156B27	6W	DC48V	2700K	White	460	36°	90	20
LHLMM1512N27	12W	DC48V	2700K	Black	1000	36°	90	20
LHLMM1512B27	12W	DC48V	2700K	White	1000	36°	90	20
LHLMM1518N27	18W	DC48V	2700K	Black	1400	36°	90	20
LHLMM1518B27	18W	DC48V	2700K	White	1400	36°	90	20
LHLMM1524N27	24W	DC48V	2700K	Black	2000	36°	90	20
LHLMM1524B27	24W	DC48V	2700K	White	2000	36°	90	20
LHLMM156N30	6W	DC48V	3000K	Black	460	36°	90	20
LHLMM156B30	6W	DC48V	3000K	White	460	36°	90	20
LHLMM1512N30	12W	DC48V	3000K	Black	1000	36°	90	20
LHLMM1512B30	12W	DC48V	3000K	White	1000	36°	90	20
LHLMM1518N30	18W	DC48V	3000K	Black	1400	36°	90	20
LHLMM1518B30	18W	DC48V	3000K	White	1400	36°	90	20
LHLMM1524N30	24W	DC48V	3000K	Black	2000	36°	90	20
LHLMM1524B30	24W	DC48V	3000K	White	2000	36°	90	20
LHLMM156N40	6W	DC48V	4000K	Black	460	36°	90	20
LHLMM156B40	6W	DC48V	4000K	White	460	36°	90	20
LHLMM1512N40	12W	DC48V	4000K	Black	1000	36°	90	20
LHLMM1512B40	12W	DC48V	4000K	White	1000	36°	90	20
LHLMM1518N40	18W	DC48V	4000K	Black	1400	36°	90	20
LHLMM1518B40	18W	DC48V	4000K	White	1400	36°	90	20
LHLMM1524N40	24W	DC48V	4000K	Black	2000	36°	90	20
LHLMM1524B40	24W	DC48V	4000K	White	2000	36°	90	20
BLUETOOTH - CCT								
LHLMM156NTNTB	6W	DC48V	2700K ~ 6000K	Black	460	36°	90	20
LHLMM156BTNTB	6W	DC48V	2700K ~ 6000K	White	460	36°	90	20
LHLMM1512NTNTB	12W	DC48V	2700K ~ 6000K	Black	1000	36°	90	20
LHLMM1512BTNTB	12W	DC48V	2700K ~ 6000K	White	1000	36°	90	20
LHLMM1518NTNTB	18W	DC48V	2700K ~ 6000K	Black	1400	36°	90	20
LHLMM1518BTNTB	18W	DC48V	2700K ~ 6000K	White	1400	36°	90	20
LHLMM1524NTNTB	24W	DC48V	2700K ~ 6000K	Black	2000	36°	90	20
LHLMM1524BTNTB	24W	DC48V	2700K ~ 6000K	White	2000	36°	90	20