



MATRIX XS SQUARE



Description

Mini square downlight of super reduced size and minimalst design, with high visual comfort and made up of individual optical modules.

Body made of die-cast aluminum with high dissipation performance that provides excellent heat evacuation.

IP20 protection grade

Reflector manufactured in polycarbonate with gloss black and gloss white finish ensuring minimum glare.

24° aperture lens with UGR<9 low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

OSRAM brand SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperature of 3000K.

Driver included with power factor 0.90(PF).

Voltage supply 220-240V / 50-60Hz.

Mounting in false ceilings adaptable to all types of modular and plaster ceilings.

Temperature

3000K

Usage

Designed for general and accent lighting applications that integrates into all types of modern, domestic, hotel, commercial, restaurant, office and residential spaces.

Colors

● White - Black ● Black-Black

Versions

*Optional adjustment , DALI, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.




MATRIX XS SQUARE 5

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHMXS15BN30	5W	AC220-240V	3000K	White-Black	390	24°	90	20
LHMXS15NN30	5W	AC220-240V	3000K	Black-Black	390	24°	90	20
REGULATIONS								
TRIAC								
LHMXS15BN30T	5W	AC220-240V	3000K	White-Black	390	24°	90	20
LHMXS15NN30T	5W	AC220-240V	3000K	Black-Black	390	24°	90	20
0-10V								
LHMXS15BN300	5W	AC220-240V	3000K	White-Black	390	24°	90	20
LHMXS15NN300	5W	AC220-240V	3000K	Black-Black	390	24°	90	20
CASAMBI								
LHMXS15BN30C	5W	AC220-240V	3000K	White-Black	390	24°	90	20
LHMXS15NN30C	5W	AC220-240V	3000K	Black-Black	390	24°	90	20
DALI								
LHMXS15BN30D	5W	AC220-240V	3000K	White-Black	390	24°	90	20
LHMXS15NN30D	5W	AC220-240V	3000K	Black-Black	390	24°	90	20
BLUETOOTH								
LHMXS15BN30B	5W	AC220-240V	3000K	White-Black	390	24°	90	20
LHMXS15NN30B	5W	AC220-240V	3000K	Black-Black	390	24°	90	20
ZIGBEE								
LHMXS15BN30Z	5W	AC220-240V	3000K	White-Black	390	24°	90	20
LHMXS15NN30Z	5W	AC220-240V	3000K	Black-Black	390	24°	90	20

ACCESSORIES

LHPTC181224	TRIAC TO CASAMBI SIGNAL CONVERTER PICKUP MAXIMUM 150W
LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTTRIACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Dimensions



Luminous Flow

