

MODENA S 20

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHTL520B22	20W	AC220-240V	2200K	White	2400	40°	95	20
LHTL520B27	20W	AC220-240V	2700K	White	2400	40°	95	20
LHTL520B30	20W	AC220-240V	3000K	White	2400	40°	95	20
LHTL520B35	20W	AC220-240V	3500K	White	2400	40°	95	20
LHTL520B40	20W	AC220-240V	4000K	White	2400	40°	95	20
LHTL520B50	20W	AC220-240V	5000K	White	2400	40°	95	20
LHTL520B8R	20W	AC220-240V	BREAD	White	1490	40°	82	20
LHTL520BME	20W	AC220-240V	MEAT	White	1340	40°	87	20
LHTL520BVE	20W	AC220-240V	VEGETABLE	White	1933	40°	70	20
LHTL520BWE	20W	AC220-240V	FISH	White	1150	40°	75	20
LHTL520N22	20W	AC220-240V	2200K	Black	2400	40°	95	20
LHTL520N27	20W	AC220-240V	2700K	Black	2400	40°	95	20
LHTL520N30	20W	AC220-240V	3000K	Black	2400	40°	95	20
LHTL520N35	20W	AC220-240V	3500K	Black	2400	40°	95	20
LHTL520N40	20W	AC220-240V	4000K	Black	2400	40°	95	20
LHTL520N50	20W	AC220-240V	5000K	Black	2400	40°	95	20
LHTL520N8R	20W	AC220-240V	BREAD	Black	1490	40°	95	20
LHTL520NME	20W	AC220-240V	MEAT	Black	1340	40°	87	20
LHTL520NVE	20W	AC220-240V	VEGETABLE	Black	1933	40°	95	20
LHTL520NWE	20W	AC220-240V	FISH	Black	1150	40°	75	20

*Optional chip in CRI95 in 3200K Y 6000K

REGULATIONS

Reference	Color	Temperature	Reference	Color	Temperature
TRIAC					
LHTL520B22T-22T-35T-50T		2200K - 2700K-3500K-5000K	LHTL520B22C-27C-35C-50C		2200K - 2700K-3500K-5000K
LHTL520B30T-40T	White	3000K - 4000K	LHTL520B30C-40C	White	3000K - 4000K
LHTL520B8RT-MET-VET-WET		FOOD	LHTL520B8RC-MEC-VEC-WEC		FOOD
LHTL520N22T-27T-35T-50T		2200K - 2700K-3500K-5000K	LHTL520N22C-27C-35C-50C		2200K - 2700K-3000K-5000K
LHTL520N30T-40T	Black	3000K - 4000K	LHTL520N30C-40C	Black	3000K - 4000K
LHTL520N8RT-MET-VET-WET		FOOD	LHTL520N8RC-MEC-VEC-WEC		FOOD

DALI

LHTL520B22D-27D-35D-50D		2200K - 2700K-3500K-5000K
LHTL520B30D-40D	White	3000K - 4000K
LHTL520B8RD-MED-VED-WED		FOOD
LHTL520N22D-27D-35D-50D		2200K - 2700K-3500K-5000K
LHTL520N30D-40D	Black	3000K - 4000K
LHTL520N8RD-MED-VED-WED		FOOD

*Optional DALI+CCT. EX. REF LHTL520BTNTD.

DIFFUSERS

LHTL540DOPAL	OPAL DIFFUSER
LHTL540DELIP	ELIPTICAL DIFFUSER

CASAMBI

LHTL520B22C-27C-35C-50C		2200K - 2700K-3500K-5000K
LHTL520B30C-40C	White	3000K - 4000K
LHTL520B8RC-MEC-VEC-WEC		FOOD
LHTL520N22C-27C-35C-50C		2200K - 2700K-3000K-5000K
LHTL520N30C-40C	Black	3000K - 4000K
LHTL520N8RC-MEC-VEC-WEC		FOOD

*Optional regulation 0-10V DIMMER ON BOARD . EX. REF LHTL520B400


OPTICS

LHTL540R18	OPTIC 18 DEGREE
LHTL540R24	OPTIC 24 DEGREE
LHTL540R60	OPTIC 60 DEGREE

BASES

LHBS16EMPB	RECESSED BASE WHITE
LHBS16MPN	SURFACE BASE BLACK
LHBS16SUPB	RECESSED BASE WHITE
LHBS16SUPN	SURFACE BASE BLACK

Dimensions



ledshomelighting.es



Opal Diffuser



Elliptical Diffuser

Luminous Flow

