

ONYX WALL WASHER



Description

Recessed, wallwasher downlight with a high level of visual comfort formed by individual 10W optical modules with a super-small longitudinal design.

Body made of die-cast aluminum with high dissipation performance that provides excellent heat evacuation.

IP20 protection grade

Low glare lens with symmetrical light distribution and that provides a homogeneous illumination over the entire surface.

Optical wallwasher with UGR<12 low glare and symmetrical light distribution, providing homogeneous illumination over the entire surface.

SMD Led Chip with Color Rendering Index 90 (CRI) available in color temperatures of 2700K, 3200K and 4000K.

Driver included with power factor 0.90(PF). Voltage supply 220-240V / 50-60Hz.

Mounting in false ceilings adaptable to all types of modular and plaster ceilings.

Usage

Designed for general and accent lighting applications that integrates into all types of modern, domestic, hotel, commercial, restaurant, office and residential spaces.

Colors

- Black - Transparent
- White - Transparent

Versions

* Optional adjustment, Dali, 0-10V, PWM, PUSH DIM, DIP SWITCH, TRIAC, CASAMBI, BLUETOOTH Y ZIGBEE.


Temperature



ONYX 10 WALL WASHER

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHOLW110BCCT	10W	AC220-240V	2700K ~3200K~ 4000K	White	890	Wall Washer	90	20
LHOLW110NCCT	10W	AC220-240V	2700K ~3200K~ 4000K	Black	890	Wall Washer	90	20
REGULATIONS								
TRIAC								
Reference	Temperature		Color	P.V.P				
LHOLW110BCCTT	2700K ~3200K~ 4000K		White	71,00€				
LHOLW110NCCTT	2700K ~3200K~ 4000K		Black	71,00€				
DALI								
Reference	Temperature		Color	P.V.P				
LHOLW110BCCTD	2700K ~3200K~ 4000K		White	71,00€				
LHOLW110NCCTD	2700K ~3200K~ 4000K		Black	71,00€				
DALI + CCT								
Reference	Temperature		Color					
LHOLW110BCCTTND	2700K ~3200K~ 4000K		White					
LHOLW110NCCTTND	2700K ~3200K~ 4000K		Black					
BLUETOOTH								
Reference	Temperature		Color	P.V.P				
LHOLW110BCCTB	2700K ~3200K~ 4000K		White	76,00€				
LHOLW110NCCTB	2700K ~3200K~ 4000K		Black	76,00€				
BLUETOOTH + CCT								
Reference	Temperature		Color					
LHOLW110BCCTTNB	2700K ~3200K~ 4000K		White					
LHOLW110NCCTTNB	2700K ~3200K~ 4000K		Black					
ZIGBEE								
Reference	Temperature		Color	P.V.P				
LHOLW110BCCTZ	2700K ~3200K~ 4000K		White	83,00€				
LHOLW110NCCTZ	2700K ~3200K~ 4000K		Black	83,00€				
ZIGBEE + CCT								
Reference	Temperature		Color					
LHOLW110BCCTTNZ	2700K ~3200K~ 4000K		White					
LHOLW110NCCTTNZ	2700K ~3200K~ 4000K		Black					
CASAMBI								
Reference	Temperature		Color	P.V.P				
LHOLW110BCCTC	2700K ~3200K~ 4000K		White	136,00€				
LHOLW110NCCTC	2700K ~3200K~ 4000K		Black	136,00€				
CASAMBI + CCT								
Reference	Temperature		Color					
LHOLW110BCCTTNC	2700K ~3200K~ 4000K		White					
LHOLW110NCCTTNC	2700K ~3200K~ 4000K		Black					

Dimensions



Luminous Flow

