

PALERMO WALL WASHER



Description

Track spotlight with a 40W three-phase adapter integrated into the driver, featuring a minimalist, cylindrical design, ideal for lighting domestic, commercial, restaurant, and hospitality spaces.

The body is made of cast aluminum, with high heat dissipation performance, providing excellent heat dissipation.

IP20 protection grade.

Wall washer optic (60°) with symmetrical light distribution, providing homogeneous or accent lighting depending on your needs.

TYF brand COB LED chips with a Color Rendering Index of 95 (CRI) are available in color temperatures of 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, 6000K, and special power supplies.

Integrated Lifud driver with a 0.95 power factor (PF) adapter.

Voltage supply: 230V / 50-60Hz.

Mounting on a three-phase track using a universal track adapter.

Usage

Designed for general and accent lighting applications in all types of commercial spaces, including showrooms, car dealerships, and churches.

Colors

☐ White ☒ Black

Versions

*Optional adjustment DALI, CASAMBI Y TRIAC.

Special temperature



2200K



2700K



3000K



3500K



5000K



6000K



Tunable



RGB CCT



PALERMO WALL WASHER


Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHTLW1640B22	40W	AC220-240V	2200K	White	4660	60°	95	20
LHTLW1640B27	40W	AC220-240V	2700K	White	4660	60°	95	20
LHTLW1640B30	40W	AC220-240V	3000K	White	4660	60°	95	20
LHTLW1640B35	40W	AC220-240V	3500K	White	4660	60°	95	20
LHTLW1640B40	40W	AC220-240V	4000K	White	4660	60°	95	20
LHTLW1640B50	40W	AC220-240V	5000K	White	4660	60°	95	20
LHTLW1640B60	40W	AC220-240V	6000K	White	4660	60°	95	20
LHTLW1640BME	40W	AC220-240V	MEAT	White	4660	60°	95	20
LHTLW1640BWE	40W	AC220-240V	FISH	White	4660	60°	95	20
LHTLW1640N22	40W	AC220-240V	2200K	Black	4660	60°	95	20
LHTLW1640N27	40W	AC220-240V	2700K	Black	4660	60°	95	20
LHTLW1640N30	40W	AC220-240V	3000K	Black	4660	60°	95	20
LHTLW1640N35	40W	AC220-240V	3500K	Black	4660	60°	95	20
LHTLW1640N40	40W	AC220-240V	4000K	Black	4660	60°	95	20
LHTLW1640N50	40W	AC220-240V	5000K	Black	4660	60°	95	20
LHTLW1640N60	40W	AC220-240V	6000K	Black	4660	60°	95	20
LHTLW1640NME	40W	AC220-240V	MEAT	Black	4660	60°	95	20
LHTLW1640NWE	40W	AC220-240V	FISH	Black	4660	60°	95	20

REGULATIONS

Reference	Color	Temperature	P.V.P	Reference	Color	Temperature
TRIAC						
LHTLW1640B22T-27T-35T	White	2200K - 2700K-3500K	90,00€	LHTLW1640B22C-27C-35C	White	2200K - 2700K-3500K
LHTLW1640B30T-40T	White	3000K- 4000K	90,00€	LHTLW1640B30C-40C	White	3000K- 4000K
LHTLW1640B50T-60T	White	5000K-6000K	90,00€	LHTLW1640B50C-60C	White	5000K-6000K
LHTLW1640BMET-WET	White	FOOD	90,00€	LHTLW1640BMEC-WEC	White	FOOD
LHTLW1640N22T-27T-35T	Black	2200K - 2700K-3500K	90,00€	LHTLW1640N22C-27C-35C	Black	2200K - 2700K-3500K
LHTLW1640N30T-40T	Black	3000K- 4000K	90,00€	LHTLW1640N30C-40C	Black	3000K- 4000K
LHTLW1640N50T-60T	Black	5000K-6000K	90,00€	LHTLW1640N50C-60C	Black	5000K-6000K
LHTLW1640NMET-WET	Black	FOOD	90,00€	LHTLW1640NMEC-WEC	Black	FOOD
DAU						
LHTLW1640B22D-27D-35D	White	2200K - 2700K-3500K	131,00€	LHTLW1640B22O-27O-35O	White	2200K - 2700K-3500K
LHTLW1640B30D-40D	White	3000K- 4000K	117,00€	LHTLW1640B30O-40O	White	3000K- 4000K
LHTLW1640B50D-60D	White	5000K-6000K	131,00€	LHTLW1640B50O-60O	White	5000K-6000K
LHTLW1640BMED-WED	White	FOOD	141,00€	LHTLW1640BMEO-WEO	White	FOOD
LHTLW1640N22D-27D-35D	Black	2200K - 2700K-3500K	131,00€	LHTLW1640N22O-27O-35O	Black	2200K - 2700K-3500K
LHTLW1640N30D-40D	Black	3000K- 4000K	117,00€	LHTLW1640N30O-40O	Black	3000K- 4000K
LHTLW1640N50D-60D	Black	5000K-6000K	131,00€	LHTLW1640N50O-60O	Black	5000K-6000K
LHTLW1640NMED-WED	Black	FOOD	141,00€	LHTLW1640NMEO-WEO	Black	FOOD

*Optional DAU+CCT. EX. REF LHTLW1640BTND

Dimensions



Luminous Flow

