

PICCOLO



Description

Track spotlight with integrated driver in the three-phase 12W adapter with circular and minimalist design, ideal for lighting domestic, commercial, catering and hospitality spaces.

Body and frame made of die-cast aluminum, independent aluminum heatsink with high dissipation performance providing excellent heat dissipation.

IP20 protection grade

15°, 24°, 36° and 50° optics and lenses with symmetrical light distribution, providing homogeneous or accent lighting as required.

CREE brand COB LED chip with Color Rendering Index 92 (CRI) supplied in color temperatures of 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, and 6000K.

Philips driver integrated in the adapter with power factor 0.95 (PF).

Voltage supply 230V / 50-60Hz.

Three-phase rail mounting by means of a universal rail adapter.

Usage

Designed for general and accent lighting applications that integrates into all types of commercial spaces, showrooms, car dealerships and churches.

Colors

○ White ● Black

Versions

*Optional adjustment DALI, CASAMBI Y TRIAC.

Special temperature



PICCOLO 10

Reference	Consumption	Voltage	Temperature	Color	Lumens	Δ	CRI	IP
ON-OFF								
LHTLP1510N22	10W	AC220-240V	2200K	Black	600	36°	92	20
LHTLP1510N27	10W	AC220-240V	2700K	Black	600	36°	92	20
LHTLP1510N30	10W	AC220-240V	3000K	Black	600	36°	92	20
LHTLP1510N35	10W	AC220-240V	3500K	Black	600	36°	92	20
LHTLP1510N40	10W	AC220-240V	4000K	Black	600	36°	92	20
LHTLP1510N50	10W	AC220-240V	5000K	Black	600	36°	92	20
LHTLP1510N60	10W	AC220-240V	6000K	Black	600	36°	92	20
LHTLP1510B22	10W	AC220-240V	2200K	White	600	36°	92	20
LHTLP1510B27	10W	AC220-240V	2700K	White	600	36°	92	20
LHTLP1510B30	10W	AC220-240V	3000K	White	600	36°	92	20
LHTLP1510B35	10W	AC220-240V	3500K	White	600	36°	92	20
LHTLP1510B40	10W	AC220-240V	4000K	White	600	36°	92	20
LHTLP1510B50	10W	AC220-240V	5000K	White	600	36°	92	20
LHTLP1510B60	10W	AC220-240V	6000K	White	600	36°	92	20

REGULATIONS

Reference	Color	Temperature
-----------	-------	-------------

TRIAC

LHTLP1510N22T-27T-35T	Black	2200K-2700K-3500K
LHTLP1510N30T-40T	Black	3000K-4000K
LHTLP1510N50T-60T	Black	5000K-6000K
LHTLP1510B22T-27T-35T	White	2200K-2700K-3500K
LHTLP1510B30T-40T	White	3000K-4000K
LHTLP1510B50T-60T	White	5000K-6000K

DALI

LHTLP1510N22D-27D-35D	Black	2200K-2700K-3500K
LHTLP1510N30D-40D	Black	3000K-4000K
LHTLP1510N50D-60D	Black	5000K-6000K
LHTLP1510B22D-27D-35D	White	2200K-2700K-3500K
LHTLP1510B30D-40D	White	3000K-4000K
LHTLP1510B50D-60D	White	5000K-6000K

*Optional DALI+CCT. EX. REF LHTLP1510B1NTD. OPTICS

LHTLP1510R15 15 DEGREE OPTICS
LHTLP1510R24 24 DEGREE OPTICS
LHTLP1510R50 50 DEGREE OPTICS

Reference	Color	Temperature
-----------	-------	-------------

CASAMBI

LHTLP1510N22C-27C-35C	Black	2200K-2700K-3500K
LHTLP1510N30C-40C	Black	3000K-4000K
LHTLP1510N50C-60C	Black	5000K-6000K
LHTLP1510B22C-27C-35C	White	2200K-2700K-3500K
LHTLP1510B30C-40C	White	3000K-4000K
LHTLP1510B50C-60C	White	5000K-6000K


0-10V DIMMER ON BOARD

LHTLP1510N220-270-350	Black	2200K-2700K-3500K
LHTLP1510N300-400	Black	3000K-4000K
LHTLP1510N500-600	Black	5000K-6000K
LHTLP1510B220-270-350	White	2200K-2700K-3500K
LHTLP1510B300-400	White	3000K-4000K
LHTLP1510B500-600	White	5000K-6000K

BASES

LHBS16MPB RECESSED BASE WHITE
LHBS16MPN SURFACE BASE BLACK
LHBS16SUPB RECESSED BASE WHITE
LHBS16SUPN SURFACE BASE BLACK

Dimensions



Luminous Flow

