

PICCOLO



Description

Track spotlight with integrated driver in the three-phase 15W adapter with circular and minimalist design, ideal for lighting domestic, commercial, catering and hospitality spaces.

Body and frame made of die-cast aluminum, independent aluminum heatsink with high dissipation performance providing excellent heat dissipation.

IP20 protection grade

15°, 24°, 36° and 50° optics and lenses with symmetrical light distribution, providing homogeneous or accent lighting as required.

CREE brand COB LED chip with Color Rendering Index 92 (CRI) supplied in color temperatures of 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, and 6000K.

Philips driver integrated in the adapter with power factor 0.95 (PF).

Voltage supply 230V / 50-60Hz.

Three-phase rail mounting by means of a universal rail adapter.

Special temperature



Usage

Designed for general and accent lighting applications that integrates into all types of commercial spaces, showrooms, car dealerships and churches.

Colors

○ White ● Black

Versions

*Optional adjustment DALI, CASAMBI Y TRIAC.



PICCOLO 15

Reference	Consumption	Voltage	Temperature	Color	Lumens	Δ	CRI	IP
ON-OFF								
LHTLP1515N22	15W	AC220-240V	2200K	Black	890	36°	92	20
LHTLP1515N27	15W	AC220-240V	2700K	Black	890	36°	92	20
LHTLP1515N30	15W	AC220-240V	3000K	Black	890	36°	92	20
LHTLP1515N35	15W	AC220-240V	3500K	Black	890	36°	92	20
LHTLP1515N40	15W	AC220-240V	4000K	Black	890	36°	92	20
LHTLP1515N50	15W	AC220-240V	5000K	Black	890	36°	92	20
LHTLP1515N60	15W	AC220-240V	6000K	Black	890	36°	92	20
LHTLP1515B22	15W	AC220-240V	2200K	White	890	36°	92	20
LHTLP1515B27	15W	AC220-240V	2700K	White	890	36°	92	20
LHTLP1515B30	15W	AC220-240V	3000K	White	890	36°	92	20
LHTLP1515B35	15W	AC220-240V	3500K	White	890	36°	92	20
LHTLP1515B40	15W	AC220-240V	4000K	White	890	36°	92	20
LHTLP1515B50	15W	AC220-240V	5000K	White	890	36°	92	20
LHTLP1515B60	15W	AC220-240V	6000K	White	890	36°	92	20

REGULATIONS

Reference	Color	Temperature	Reference	Color	Temperature
TRIAC					
LHTLP1515N22T-27T-35T	Black	2200K-2700K-3500K	LHTLP1515N22C-27C-35C	Black	2200K-2700K-3500K
LHTLP1515N30T-40T	Black	3000K-4000K	LHTLP1515N30C-40C	Black	3000K-4000K
LHTLP1515N50T-60T	Black	5000K-6000K	LHTLP1515N50C-60C	Black	5000K-6000K
LHTLP1515B22T-27T-35T	White	2200K-2700K-3500K	LHTLP1515B22C-27C-35C	White	2200K-2700K-3500K
LHTLP1515B30T-40T	White	3000K-4000K	LHTLP1515B30C-40C	White	3000K-4000K
LHTLP1515B50T-60T	White	5000K-6000K	LHTLP1515B50C-60C	White	5000K-6000K
DALI					
LHTLP1515N22D-27D-35D	Black	2200K-2700K-3500K	LHTLP1515N220-270-350	Black	2200K-2700K-3500K
LHTLP1515N30D-40D	Black	3000K-4000K	LHTLP1515N300-400	Black	3000K-4000K
LHTLP1515N50D-60D	Black	5000K-6000K	LHTLP1515N500-600	Black	5000K-6000K
LHTLP1515B22D-27D-35D	White	2200K-2700K-3500K	LHTLP1515B220-270-350	White	2200K-2700K-3500K
LHTLP1515B30D-40D	White	3000K-4000K	LHTLP1515B300-400	White	3000K-4000K
LHTLP1515B50D-60D	White	5000K-6000K	LHTLP1515B500-600	White	5000K-6000K


*Optional DALI+CCT. EX. REF LHTLP1515B1NTMD. OPTICS

LHTLC1515R15 15 DEGREE OPTICS
LHTLC1515R24 24 DEGREE OPTICS
LHTLC1515R50 50 DEGREE OPTICS

BASES

LHBS16MPB RECESSED BASE WHITE
LHBS16MPN SURFACE BASE BLACK
LHBS16SUPB RECESSED BASE WHITE
LHBS16SUPN SURFACE BASE BLACK

Dimensions



Luminous Flow

