

TUBE

Reference	Consumption	Voltage	Temperature	Lumens	Δ _α	CRI	IP
ON-OFF							
LHlTM1518N27	18W	DC48V	2700K	1100	120°	90	20
LHlTM1524N27	24W	DC48V	2700K	1600	120°	90	20
LHlTM1530N27	30W	DC48V	2700K	2000	120°	90	20
LHlTM1518N30	18W	DC48V	3000K	1100	120°	90	20
LHlTM1524N30	24W	DC48V	3000K	1600	120°	90	20
LHlTM1530N30	30W	DC48V	3000K	2000	120°	90	20
DAU							
LHlTM1518N27D	18W	DC48V	2700K	1100	120°	90	20
LHlTM1524N27D	24W	DC48V	2700K	1600	120°	90	20
LHlTM1530N27D	30W	DC48V	2700K	2000	120°	90	20
LHlTM1518N30D	18W	DC48V	3000K	1100	120°	90	20
LHlTM1524N30D	24W	DC48V	3000K	1600	120°	90	20
LHlTM1530N30D	30W	DC48V	3000K	2000	120°	90	20
BLUETOOTH - CCT							
LHlTM1518NTNTB	18W	DC48V	2700K ~ 6000K	1100	120°	90	20
LHlTM1524NTNTB	24W	DC48V	2700K ~ 6000K	1600	120°	90	20
LHlTM1530NTNTB	30W	DC48V	2700K ~ 6000K	2000	120°	90	20

*Luminaire compatible with TRACKS MAGNET XS DC48V SURFACE.

Dimensions

