

VENICE SURFACE



Description

Surface downlight of 6W with cylindrical and minimalist design, ideal for lighting all types of small domestic, commercial, catering and hospitality spaces.

Body made of die-cast aluminum with high dissipation performance providing excellent heat dissipation. IP20 protection grade.

Reflector manufactured in polycarbonate with black gloss finish and transparent glass diffuser.

70° aperture optics with UGR<16 low glare and symmetrical light providing both homogeneous or accent lighting as required.

TYF brand SMD Led Chip with Color Rendering Index 95 (CRI) available in color temperature of 2200K, 2700K, 3000K, 3200K, 3500K, 4000K, 5000K, 6000K and adjustable 2700K~ 6000K.

LIFUD driver included with power factor 0.95(PF).

Voltage supply 230V / 50-60Hz.

Surface mounting.

Usage

Designed for general accent lighting for all types of spaces.

Colors

○ White ● Black

Versions

*Optional adjustment
DALI, CASAMBI, BLUETOOTH Y
ZIGBEE version 20W.

Special temperature



VENICE SURFACE 6

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDS156B22	6W	AC220-240V	2200K	White	550	24°	90	20
LHDS156B27	6W	AC220-240V	2700K	White	550	24°	90	20
LHDS156B30	6W	AC220-240V	3000K	White	550	24°	90	20
LHDS156B35	6W	AC220-240V	3500K	White	550	24°	90	20
LHDS156B40	6W	AC220-240V	4000K	White	550	24°	90	20
LHDS156N22	6W	AC220-240V	2200K	Black	550	24°	90	20
LHDS156N27	6W	AC220-240V	2700K	Black	550	24°	90	20
LHDS156N30	6W	AC220-240V	3000K	Black	550	24°	90	20
LHDS156N35	6W	AC220-240V	3500K	Black	550	24°	90	20
LHDS156N40	6W	AC220-240V	4000K	Black	550	24°	90	20

REGULATIONS EN REMOTE

Reference	Temperature	Color	Reference	Temperature	Color
TRIAC - REMOTE ASSEMBLY					
LHDS156B22T-27T-35T	2200K-2700K-3500K	White	LHDS156B22-27-35	2200K-2700K-3500K	White
LHDS156B30T-B40T	3000K-4000K	White	LHDS156B300-B400	3000K-4000K	White
LHDS156N22T-27T-35T	2200K-2700K-3500K	Black	LHDS156N220-270-350	2200K-2700K-3500K	Black
LHDS156N30T-B40T	3000K-4000K	Black	LHDS156N300-B400	3000K-4000K	Black

DALI - REMOTE ASSEMBLY

LHDS156B22D-27D-35D	2200K-2700K-3500K	White	LHDS156B22B-27B-35B	2200K-2700K-3500K	White
LHDS156B30D-B40D	3000K-4000K	White	LHDS156B30B-B40B	3000K-4000K	White
LHDS156N22D-27D-35D	2200K-2700K-3500K	Black	LHDS156N22B-27B-35B	2200K-2700K-3500K	Black
LHDS156N30D-B40D	3000K-4000K	Black	LHDS156N30B-B40B	3000K-4000K	Black

*Optional DALI+CCT. EX. REF LHDS156B22TNTD. add 23,00€ to the P.V.P


ZIGBEE - REMOTE ASSEMBLY

LHDS156B22Z-27Z-35Z	700K-3500K	White	LHDS156R15	15 DEGREE OPTICS
LHDS156B30Z-B40Z	3000K-4000K	White	LHDS156R38	38 DEGREE OPTICS
LHDS156N22Z-27Z-35Z	2200K-2700K-3500K	Black	LHDS156R60	60 DEGREE OPTICS
LHDS156N30Z-B40Z	3000K-4000K	Black		

*Optional ZIGBEE+CCT. EX. REF LHDS156B22TNTZ ACCESSORIES

LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTRIACZG	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Dimensions



Luminous Flow

