



CAPRI



Description

Track spotlight with driver integrated in the 10W three-phase adapter with a cylindrical and minimalist design, ideal for lighting domestic, commercial, catering and hospitality spaces.

Body and frame made of die-cast aluminum, independent aluminum heatsink with high dissipation performance providing excellent heat dissipation.

IP20 protection grade.

15°, 24° and 36° optics and lenses with symmetrical light distribution, providing homogeneous or accent lighting as required.

TYF brand COB LED chip with Color Rendering Index 95 (CRI) supplied in color temperatures of 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, and 6000K and special food temperatures of 20W, 30W, and 40W.

PHILIPS driver integrated in the adapter with power factor 0.95 (PF).

Voltage supply 230V / 50-60Hz.

Three-phase rail mounting by means of universal rail adapter.

Special temperature



Usage

Designed for general and accent lighting applications that integrates into all types of commercial spaces, showrooms, car dealerships and churches.

Colors

○ White ● Black

Versions

*Optional adjustment DALI, CASAMBI Y TRIAC.

Accessories



CAPRI 10

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHTL610B22	10W	AC220-240V	2200K	White	1145	36°	95	20
LHTL610B27	10W	AC220-240V	2700K	White	1145	36°	95	20
LHTL610B30	10W	AC220-240V	3000K	White	1145	36°	95	20
LHTL610B35	10W	AC220-240V	3500K	White	1145	36°	95	20
LHTL610B40	10W	AC220-240V	4000K	White	1145	36°	95	20
LHTL610B50	10W	AC220-240V	5000K	White	1145	36°	95	20
LHTL610N22	10W	AC220-240V	2200K	Black	1145	36°	95	20
LHTL610N27	10W	AC220-240V	2700K	Black	1145	36°	95	20
LHTL610N30	10W	AC220-240V	3000K	Black	1145	36°	95	20
LHTL610N35	10W	AC220-240V	3500K	Black	1145	36°	95	20
LHTL610N40	10W	AC220-240V	4000K	Black	1145	36°	95	20
LHTL610N50	10W	AC220-240V	5000K	Black	1145	36°	95	20

*Optional chip in CRI95 in 3200K Y 6000K

REGULATIONS

Reference	Color	Temperature
TRIAC		
LHTL610B22T-27T-35T		2200K-2700K-3500K
LHTL610B30T-40T	White	3000K-4000K
LHTL610B50T		5000K
.....		
LHTL610N22T-27T-35T		2200K-2700K-3500K
LHTL610N30T-40T	Black	3000K-4000K
LHTL610N50T		5000K

DALI

LHTL610B22D-27D-35D	White	2200K-2700K-3500K
LHTL610B30D-40D		3000K-4000K
LHTL610B50D		5000K
.....		
LHTL610N22D-27D-35D		2200K-2700K-3500K
LHTL610N30D-40D	Black	3000K-4000K
LHTL610N50D		5000K

Optional DALI+CCT. EX. REF LHTL620B1NTD. P.V.P 143,00€

ACCESSORIES

LHTL610DOPAL	OPAL DIFFUSER
LHTL610DELIP	ELIPTICAL DIFFUSER
LHTL610BSNOOT	WHITE CONCENTRATOR ACCESSORY
LHTL610NSNOOT	BLACK CONCENTRATOR ACCESSORY

Reference	Color	Temperature
CASAMBI		
LHTL610B22C-27C-35C		2200K-2700K-3500K
LHTL610B30C-40C	White	3000K-4000K
LHTL610B50C		5000K
.....		
LHTL610N22C-27C-35C		2200K-2700K-3500K
LHTL610N30C-40C	Black	3000K-4000K
LHTL610N50C		5000K

*Optional regulation 0-10V DIMMER ON BOARD . EX. REF LHTL610B400.


OPTICS

LHTL610R15	15 DEGREE OPTICS
LHTL610R24	24 DEGREE OPTICS
LHTL610R45	45 DEGREE OPTICS
LHTL610R60	60 DEGREE OPTICS

BASES

LHBS16EMPB	RECESSED BASE WHITE
LHBS16EMPB	SURFACE BASE BLACK
LHBS16SUPB	RECESSED BASE WHITE
LHBS16SUPB	SURFACE BASE BLACK

Dimensions



Luminous Flow

