



CAPRI



Description

Track spotlight with driver integrated in the 20W three-phase adapter with a cylindrical and minimalist design, ideal for lighting domestic, commercial, catering and hospitality spaces.

Body and frame made of die-cast aluminum, independent aluminum heatsink with high dissipation performance providing excellent heat dissipation.

IP20 protection grade.

15°, 24° and 36° optics and lenses with symmetrical light distribution, providing homogeneous or accent lighting as required.

TYF brand COB LED chip with Color Rendering Index 95 (CRI) supplied in color temperatures of 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, and 6000K and special food temperatures of 20W, 30W, and 40W.

PHILIPS driver integrated in the adapter with power factor 0.95 (PF).

Voltage supply 230V / 50-60Hz.

Three-phase rail mounting by means of universal rail adapter.

Special temperature



Usage

Designed for general and accent lighting applications that integrates into all types of commercial spaces, showrooms, car dealerships and churches.

Colors

○ White ● Black

Versions

*Optional adjustment DALI, CASAMBI Y TRIAC.

Accessories



CAPRI 20

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHTL620B22	20W	AC220-240V	2200K	White	2290	36°	95	20
LHTL620B27	20W	AC220-240V	2700K	White	2290	36°	95	20
LHTL620B30	20W	AC220-240V	3000K	White	2290	36°	95	20
LHTL620B35	20W	AC220-240V	3500K	White	2290	36°	95	20
LHTL620B40	20W	AC220-240V	4000K	White	2290	36°	95	20
LHTL620B50	20W	AC220-240V	5000K	White	2290	36°	95	20
LHTL620N22	20W	AC220-240V	2200K	Black	2290	36°	95	20
LHTL620N27	20W	AC220-240V	2700K	Black	2290	36°	95	20
LHTL620N30	20W	AC220-240V	3000K	Black	2290	36°	95	20
LHTL620N35	20W	AC220-240V	3500K	Black	2290	36°	95	20
LHTL620N40	20W	AC220-240V	4000K	Black	2290	36°	95	20
LHTL620N50	20W	AC220-240V	5000K	Black	2290	36°	95	20

*Optional chip in CRI95 in 3200K Y 6000K

REGULATIONS

Reference	Color	Temperature
TRIAC		
LHTL620B22T-27T-35T	White	2200K-2700K-3500K
LHTL620B30T-40T		3000K-4000K
LHTL620B50T		5000K
LHTL620N22T-27T-35T	Black	2200K-2700K-3500K
LHTL620N30T-40T		3000K-4000K
LHTL620N50T		5000K

DALI

LHTL620B22D-27D-35D	White	2200K-2700K-3500K
LHTL620B30D-40D		3000K-4000K
LHTL620B50D		5000K
LHTL620N22D-27D-35D	Black	2200K-2700K-3500K
LHTL620N30D-40D		3000K-4000K
LHTL620N50D		5000K

*Optional DALI+CCT. EX.REF LHTL620BTNTD.

ACCESSORIES

LHTL620DOPAL	OPAL DIFFUSER
LHTL620DELIP	EIPTICAL DIFFUSER
LHTL620BSNOOT	WHITE CONCENTRATOR ACCESSORY
LHTL620NSNOOT	BLACK CONCENTRATOR ACCESSORY

Reference	Color	Temperature
CASAMBI		
LHTL620B22C-27C-35C	White	2200K-2700K-3500K
LHTL620B30C-40C		3000K-4000K
LHTL620B50T		5000K
LHTL620N22C-27C-35C	Black	2200K-2700K-3500K
LHTL620N30C-40C		3000K-4000K
LHTL620N50C		5000K

*Optional regulation 0-10V DIMMER ON BOARD. EX. REF LHTL620B400.

OPTICS

LHTL620R15	15 DEGREE OPTICS
LHTL620R24	24 DEGREE OPTICS
LHTL620R45	45 DEGREE OPTICS
LHTL620R60	60 DEGREE OPTICS

BASES

LHBS16EMPB	RECESSED BASE WHITE
LHBS16EMPN	SURFACE BASE BLACK
LHBS16SUPB	RECESSED BASE WHITE
LHBS16SUPN	SURFACE BASE BLACK

Dimensions



Luminous Flow

