

CAPRI

LedsHOME
LIGHTING

Description

Track spotlight with driver integrated in the 30W three-phase adapter with a cylindrical and minimalist design, ideal for lighting domestic, commercial, catering and hospitality spaces.

Body and frame made of die-cast aluminum, independent aluminum heatsink with high dissipation performance providing excellent heat dissipation.

IP20 protection grade.

15°, 24° and 36° optics and lenses with symmetrical light distribution, providing homogeneous or accent lighting as required.

TYF brand COB LED chip with Color Rendering Index 95 (CRI) supplied in color temperatures of 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, and 6000K and special food temperatures of 20W, 30W, and 40W.

PHILIPS driver integrated in the adapter with power factor 0.95 (PF).

Voltage supply 230V / 50-60Hz.

Three-phase rail mounting by means of universal rail adapter.

Special temperature



Usage

Designed for general and accent lighting applications that integrates into all types of commercial spaces, showrooms, car dealerships and churches.

Colors

○ White ● Black

Versions

*Optional adjustment DALI, CASAMBI Y TRIAC.

Accessories



Anti-glare grille



Snoot



Opal Diffuser



Elliptical Diffuser



CAPRI 30

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHTL630B22	30W	AC220-240V	2200K	White	3470	36°	95	20
LHTL630B27	30W	AC220-240V	2700K	White	3470	36°	95	20
LHTL630B30	30W	AC220-240V	3000K	White	3470	36°	95	20
LHTL630B35	30W	AC220-240V	3500K	White	3470	36°	95	20
LHTL630B40	30W	AC220-240V	4000K	White	3470	36°	95	20
LHTL630B50	30W	AC220-240V	5000K	White	3470	36°	95	20
LH630BME	30W	AC220-240V	MEAT	White	2200	36°	86	20
LH630BVE	30W	AC220-240V	VEGETABLE	White	2021	36°	95	20
LH630BWE	30W	AC220-240V	FISH	White	1770	36°	76	20
LH630BBR	30W	AC220-240V	BREAD	White	1777	36°	95	20
LH630N22	30W	AC220-240V	2200K	Black	3470	36°	95	20
LH630N27	30W	AC220-240V	2700K	Black	3470	36°	95	20
LH630N30	30W	AC220-240V	3000K	Black	3470	36°	95	20
LH630N35	30W	AC220-240V	3500K	Black	3470	36°	95	20
LH630N40	30W	AC220-240V	4000K	Black	3470	36°	95	20
LH630N50	30W	AC220-240V	5000K	Black	3470	36°	95	20
LH630NME	30W	AC220-240V	MEAT	Black	2200	36°	86	20
LH630NVE	30W	AC220-240V	VEGETABLE	Black	2021	36°	95	20
LH630NWE	30W	AC220-240V	FISH	Black	1770	36°	76	20
LH630NBR	30W	AC220-240V	BREAD	Black	1777	36°	95	20

*Optional chip in CRI95 in 3200K Y 6000K

REGULATIONS

Reference	Color	Temperature	Reference	Color	Temperature
TRIAC					
LH630B22T-27T-35T-50T		2200K-2700K-3500K-5000K	LH630B22C-27C-35C-50C		2200K-2700K-3500K-5000K
LH630B30T-40T	White	3500K-4000K	LH630B30C-40C	White	3500K-4000K
LH630NMET-VET-WET-BRT		FOOD	LH630NMEC-VEC-WEC-BRC		FOOD
LH630N22T-27T-35T-50T		2200K-2700K-3500K-5000K	LH630N22C-27C-35T-50T		2200K-2700K-3500K-5000K
LH630N30T-40T	Black	3500K-4000K	LH630N30C-40C	Black	3500K-4000K
LH630NMET-VET-WET-BRT		FOOD	LH630NMEC-VEC-WEC-BRC		FOOD

DALI

LH630B22D-27D-35D-50D		2200K-2700K-3500K-5000K
LH630B30D-40D	White	3500K-4000K
LH630NMED-VED-WED-BRD		FOOD
LH630N22D-27D-35D-50D		2200K-2700K-3500K-5000K
LH630N30D-40D	Black	3500K-4000K
LH630NMED-VED-WED-BRD		FOOD

*Optional DALI+CCT. EX. REF LH630BNTND.

ACCESSORIES

LH630DOPAL	OPAL DIFFUSER
LH630DELIP	ELIPTICAL DIFFUSER
LH630BSNOOT	WHITE CONCENTRATOR ACCESSORY
LH630NSNOOT	BLACK CONCENTRATOR ACCESSORY

CASAMBI

LH630B22C-27C-35C-50C	2200K-2700K-3500K-5000K
LH630B30C-40C	3500K-4000K
LH630NMEC-VEC-WEC-BRC	FOOD
LH630N22C-27C-35T-50T	2200K-2700K-3500K-5000K
LH630N30C-40C	3500K-4000K
LH630NMEC-VEC-WEC-BRC	FOOD

*Optional regulation 0-10V DIMMER ON BOARD . EX. REF LH630B400.


OPTICS

LH630R15	15 DEGREE OPTICS
LH630R24	24 DEGREE OPTICS
LH630R45	45 DEGREE OPTICS
LH630R60	60 DEGREE OPTICS

BASES

LHBS16MPB	RECESSED BASE WHITE
LHBS16MPN	SURFACE BASE BLACK
LHBS16SUPB	RECESSED BASE WHITE
LHBS16SUPN	SURFACE BASE BLACK

Dimensions



Luminous Flow

