

CAPRI

LedsHOME
LIGHTING

Description

Track spotlight with driver integrated in the 40W three-phase adapter with a cylindrical and minimalist design, ideal for lighting domestic, commercial, catering and hospitality spaces.

Body and frame made of die-cast aluminum, independent aluminum heatsink with high dissipation performance providing excellent heat dissipation.

IP20 protection grade.

15°, 24° and 36° optics and lenses with symmetrical light distribution, providing homogeneous or accent lighting as required.


TYF brand COB LED chip with Color Rendering Index 95 (CRI) supplied in color temperatures of 2200K, 2700K, 3000K, 3500K, 4000K, 5000K, and 6000K and special food temperatures of 20W, 30W, and 40W.

PHILIPS driver integrated in the adapter with power factor 0.95 (PF).

Voltage supply 230V / 50-60Hz.

Three-phase rail mounting by means of universal rail adapter.

Special temperature



Usage

Designed for general and accent lighting applications that integrates into all types of commercial spaces, showrooms, car dealerships and churches.

Colors

○ White ● Black

Versions

*Optional adjustment DALI, CASAMBI Y TRIAC.

Accessories



CAPRI 40

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHTL640B22	40W	AC220-240V	2200K	White	4750	36°	95	20
LHTL640B27	40W	AC220-240V	2700K	White	4750	36°	95	20
LHTL640B30	40W	AC220-240V	3000K	White	4750	36°	95	20
LHTL640B35	40W	AC220-240V	3500K	White	4750	36°	95	20
LHTL640B40	40W	AC220-240V	4000K	White	4750	36°	95	20
LHTL640B50	40W	AC220-240V	5000K	White	4750	36°	95	20
LHTL640BME	40W	AC220-240V	MEAT	White	2900	36°	85	20
LHTL640BVE	40W	AC220-240V	VEGETABLE	White	2817	36°	95	20
LHTL640BWE	40W	AC220-240V	FISH	White	2400	36°	76	20
LHTL640BBR	40W	AC220-240V	BREAD	White	2477	36°	95	20
LHTL640N22	40W	AC220-240V	2200K	Black	4750	36°	95	20
LHTL640N27	40W	AC220-240V	2700K	Black	4750	36°	95	20
LHTL640N30	40W	AC220-240V	3000K	Black	4750	36°	95	20
LHTL640N35	40W	AC220-240V	3500K	Black	4750	36°	95	20
LHTL640N40	40W	AC220-240V	4000K	Black	4750	36°	95	20
LHTL640N50	40W	AC220-240V	5000K	Black	4750	36°	95	20
LHTL640NME	40W	AC220-240V	MEAT	Black	2900	36°	86	20
LHTL640NVE	40W	AC220-240V	VEGETABLE	Black	2817	36°	95	20
LHTL640NWE	40W	AC220-240V	FISH	Black	2400	36°	76	20
LHTL640NBR	40W	AC220-240V	BREAD	Black	2477	36°	95	20

*Optional chip in CRI95 in 3200K and 6000K

REGULATIONS

Reference	Color	Temperature	Reference	Color	Temperature
TRIAC			CASAMBI		
LHTL640B22T-27T-35T-50T		2200K-2700K-3500K-5000K	LHTL640B22C-27C-35C-50C		2200K-2700K-3500K-5000K
LHTL640B30T-40T	White	3000K-4000K	LHTL640B30C-40C	White	3000K-4000K
LHTL640NMET-VET-WET-BRT		FOOD	LHTL640NMEC-VEC-WEC-BRC		FOOD
LHTL640N22T-27T-35T-50T		2200K-2700K-3500K-5000K	LHTL640N22C-27C-35T-50T		2200K-2700K-3500K-5000K
LHTL640N30T-40T	Black	3000K-4000K	LHTL640N30C-40C	Black	3000K-4000K
LHTL640NMET-VET-WET-BRT		FOOD	LHTL640NMEC-VEC-WEC-BRC		FOOD
DALI			*Optional regulation 0-10V DIMMER ON BOARD . EX. REF LHTL640B400.		
LHTL640B22D-27D-35D-50D		2200K-2700K-3500K-5000K	OPTICS		
LHTL640B30D-40D	White	3000K-4000K	LHTL640R15	15 DEGREE OPTICS	
LHTL640NMED-VED-WED-BRD		FOOD	LHTL640R24	24 DEGREE OPTICS	
LHTL640N22D-27D-35D-50D		2200K-2700K-3500K-5000K	LHTL640R45	45 DEGREE OPTICS	
LHTL640N30D-40D	Black	3000K-4000K	LHTL640R60	60 DEGREE OPTICS	
LHTL640NMED-VED-WED-BRD		FOOD	BASES		
*Optional DALI+CCT. EX. REF LHTL640BNTND.			LHBS16MPB	RECESSED BASE WHITE	
ACCESSORIES			LHBS16MPN	SURFACE BASE BLACK	
LHTL640DOPAL	OPAL DIFFUSER		LHBS16SUPB	RECESSED BASE WHITE	
LHTL640DELIP	ELLIPTICAL DIFFUSER		LHBS16SUPN	SURFACE BASE BLACK	
LHTL640BSNOOT	WHITE CONCENTRATOR ACCESSORY				
LHTL640NSNOOT	BLACK CONCENTRATOR ACCESSORY				

Dimensions



Luminous Flow

