

MINI LINK



Description

Mini recessed downlight with high visual comfort available in 5W and 8W wattage.

Body and frame made of cast aluminum, with high dissipation performance, allowing for excellent heat evacuation.

IP65 protection grade.

Prismatic lenses of 20°, 30° for 5w mini link and 15°, 24°, 36° and 50° for 8w mini link with low glare and symmetrical light distribution, which provides perfect accent lighting.

BRIDGELUX brand COB LED chip with Color Rendering Index 90 (CRI) that is supplied in color temperatures of 2700K, 3000K and 4000K.

Driver included with power factor 0.90 (PF).

Voltage supply 220-240V / 50-60Hz.

Assembly includes all types of false ceilings, furniture, showcases and displays.

Ceiling cut-outs: Ø30mm and Ø36mm.

Temperature



Usage

Designed for general decorative and accent lighting which integrates into all types of modern spaces including both domestic and commercial environments, hotels, homes, office spaces and restaurants.

Colors

○ White ● Black ● Grey ● Gold

*Upon request it can be made available in any paint finish.

Versions

*Optional adjustment DALI, TRIAC, 0-10V, ZIGBEE, BLUETOOTH Y CASAMBI



MINI LINK 5

Reference	Consumption	Voltage	Temperature	Color	Lumens	△	CRI	IP
ON-OFF								
LHDT225B27	5W	AC220-240V	2700K	White	225	40°	90	65
LHDT225B30	5W	AC220-240V	3000K	White	225	40°	90	65
LHDT225B40	5W	AC220-240V	4000K	White	225	40°	90	65
LHDT225N27	5W	AC220-240V	2700K	Black	225	40°	90	65
LHDT225N30	5W	AC220-240V	3000K	Black	225	40°	90	65
LHDT225N40	5W	AC220-240V	4000K	Black	225	40°	90	65
LHDT225G27	5W	AC220-240V	2700K	Grey	225	40°	90	65
LHDT225G30	5W	AC220-240V	3000K	Grey	225	40°	90	65
LHDT225G40	5W	AC220-240V	4000K	Grey	225	40°	90	65
LHDT225O27	5W	AC220-240V	2700K	Gold	225	40°	90	65
LHDT225O30	5W	AC220-240V	3000K	Gold	225	40°	90	65
LHDT225O40	5W	AC220-240V	4000K	Gold	225	40°	90	65

REGULATIONS

0-10V

VERSION 0-10V WHITE FINISH ADD "0" TO THE REFERENCE-EXAMPLE: . LHDT225B300

VERSION 0-10V BLACK - GREY - GOLD FINISH ADD "0" O THE REFERENCE-EXAMPLE: LHDT225O300.

TRIAC

VERSION TRIAC WHITE FINISH ADD "T" TO THE REFERENCE-EXAMPLE: . LHDT225B30T

VERSION TRIAC BLACK - GREY - GOLD FINISH ADD "T" TO THE REFERENCE-EXAMPLE: LHDT225O30T

DALI

VERSION DALI WHITE FINISH ADD "D" TO THE REFERENCE-EXAMPLE: . LHDT225B30D

VERSION DALI BLACK - GREY - GOLD FINISH ADD "D" TO THE REFERENCE-EXAMPLE: . LHDT225O30D

BLUETOOTH

VERSION BLUETOOTH WHITE FINISH ADD "B" TO THE REFERENCE-EXAMPLE: . LHDT225B30B

VERSION BLUETOOTH BLACK - GREY - GOLD FINISH ADD "B" A LA REFERENCIA-EXAMPLE: LHDT225O30B

ZIGBEE

VERSION ZIGBEE WHITE FINISH ADD "Z" TO THE REFERENCE-EXAMPLE: . LHDT225B30Z

VERSION ZIGBEE BLACK - GREY - GOLD FINISH ADD "Z" TO THE REFERENCE-EXAMPLE: LHDT225O30Z

CASAMBI

VERSION CASAMBI WHITE FINISH ADD "C" TO THE REFERENCE-EXAMPLE: LHDT225B30C

VERSION CASAMBI BLACK - GREY - GOLD FINISH ADD "C" TO THE REFERENCE-EXAMPLE: LHDT225O30C

ACCESSORIES

LHDT225L20	INTERCHANGEABLE 20 DEGREE OPTICAL
LHDT225L30	INTERCHANGEABLE 30 DEGREE OPTICAL
LHCN4PIN	MICROLINK/LINK MAX CONNECTOR STRIP. 4 LUMINAIRES FOR QUICK CONNECTION
LHCNCABLE	CABLE CONNECTOR STRIP 2 MTS FOR QUICK CONNECTION IN SERIES
LHMBGATZBBL	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + BLUETOOTH 5.0 MAX. 128 LUMINAIRES
LHMBGATZGET	GATEWAY UNIVERSAL REMOTE ZIGBEE 3.0 + ETHERNET MAX. 128 LUMINAIRES
LHMBPTRIACZG.	TRIAC CONVERTER DRIVER - ZIGBEE 3.0 + PUSH MAX 150W

Dimensions

